



LED T5 Batten S with switch

- Uniform, diffused light, creating a pleasant atmosphere
- Available in 300, 600, 900 and 1200 mm
- Maximum connectivity up to 10 pieces allows maximum flexibility
- Incl. power cable, connection pieces (fixed and flexible)
- Including integrated switch
- Energy saving up to 50%



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Energy Level
140043903	LED E T5 batten 600 9W S 3000K BL	TL 1x18W	9	800	89	3000	A+

Packaging Information


Item		Box			
Item Code	Item Description	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
140043903	LED E T5 batten 600 9W S 3000K BL	925x29x37	0.26	6956712666260	1
140043903	LED E T5 batten 600 9W S 3000K BL	935x165x170	6.60	6956712631718	20

Technical Specifications	
On-/Off-cycles	100,000
Dimmable	No
Beam angle	140 °
Finishing	White
Colour rendering index CRI	≥ 80
Degree of protection (IP)	IP20
Protection class	II
Control gear included	Yes
Weight (kg/pc)	0.14
Power factor	≥ 0.90

Electrical Supply	
Frequency	50/60 Hz
Nominal voltage	220-240 V
Voltage type	AC


Mechanical Properties	
Material housing	Polycarbonate

Ambient Conditions	
Operating temperature	-20 - 40 °C
Application temperature	25 °C
Storage environment	-25 - 50 °C



Dimensional Drawing (mm)

LED E T5 batten 600



Photometric Data

LED E T5 batten 600

