



## LED Ceiling Light Apollo

- Professional wall/ceiling luminaire with comfortable diffused light
- Easy installation on wall or ceiling
- LED Module Clio inside
- Bracket accessory available for easy mounting on existing installations (no new screw holes needed)
- Uniform, diffused light, creating a pleasant atmosphere
- IP44 versions also suitable for bathrooms and comparable spaces
- Energy saving up to 80% in comparison to a traditional light source



## Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Energy Level	Degree of protection (IP)	Weight (kg/pc)
520021000300	LED HC350 16W 2700K IP44 Apollo III	GLS 100W	16	1300	81	2700	A+	IP44	0.59

For more technical information, please go to the appendix.


## Accessories



140060553  
LED Module sensor CT



520098000200  
LED Apollo HC300 bracket



520098001800  
LED Apollo HC350 bracket

## Packaging Information

Item		Box			
Item Code	Item Description	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
140060553	LED Module sensor CT	40x35x80	0.06	6945730491732	1
520021000300	LED HC350 16W 2700K IP44 Apollo III	376x115x378	1.08	6956321852986	1
520098000200	LED Apollo HC300 bracket	234x86x49	0.44	6956321815387	1
520098001800	LED Apollo HC350 bracket	260x53x271	0.55	6941497706614	1

## Technical Specifications

Lifetime (L70)	30,000 h
Lifetime (L80)	20,000 h
On-/Off-cycles	100,000
Dimmability	On-Off
Beam angle	120 °
Finishing	White RAL9003
Colour rendering index CRI	≥ 80
Impact strength	IK03
Protection class	I
Risk group (EN 62471)	RG0
With control gear	Yes

## Electrical Supply


Frequency	50/60 Hz
Nominal voltage	220-240 V
	AC
DC input voltage	No

## Mechanical Properties

Material housing	Steel
Optical material	Polycarbonate

## Ambient Conditions

Operating temperature	-20 ~ 45 °C
Application temperature	25 °C
Storage environment	-25 ~ 50 °C



## Dimensional Drawing (mm)

