



LED Ceiling Light Apollo

- NEW: 22W dimmable version available
- NEW: bracket accessory for easy mounting on existing installations (no new screw holes needed)
- Easy installation on wall or ceiling
- LED Module Clio inside (12W and 16W)
- Uniform, diffused light, creating a pleasant atmosphere
- IP44 versions also suitable for bathrooms and comparable spaces
- Energy saving up to 80% in comparison to a traditional light source



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Energy Level	Weight (kg/pc)
520021000800	LED HC350 22W DIM 4000K IP44 Apollo	GLS 100W	22	1600	73	4000	A+	0.59

See appendix 1 for dimmer compatibility list

Packaging Information

Item		Box			
Item Code	Item Description	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
520021000800	LED HC350 22W DIM 4000K IP44 Apollo	376x115x378	0.94	6956321818647	1

Technical Specifications	
Lifespan (L70B50)	30,000 h
Lifespan (L80B50)	20,000 h
On-/Off-cycles	100,000
Dimmable	Yes (DIM)
Beam angle	120 °
Finishing	White RAL9003
Colour rendering index CRI	≥ 80
Degree of protection (IP)	IP44
Protection class	I
Risk group	RG0
Control gear included	Yes

Electrical Supply	
Frequency	50/60 Hz
Nominal voltage	220-240 V AC
DC input voltage	No

Mechanical Properties	
Material housing	Steel
Optical material	Polycarbonate

Ambient Conditions	
Operating temperature	-20 ~ 45 °C
Application temperature	25 °C
Storage environment	-25 ~ 50 °C



Dimensional Drawing (mm)

Photometric Data

LED HC350 22W DIM 4000K IP44 Apollo

