



ATLD/IP65/SC

Twistlock GU10 50W IP65 Downlight Satin Chrome



Features

IP65 downlight suitable for bathroom use.

Die-cast aluminium construction with clear glass.

Permanent earth on stirrup bracket for GU10 mains earthing.

Generous size of terminal housing for ease of wiring.

General Information

| | |
|--------------------------------|-------------------------|
| Lamp Type | GU10 |
| Colour / Finish | Satin Chrome |
| OCTO Compatibility | Smart Indoor controller |
| IP Rating | IP65 |
| Class Protection | 1 |
| Bathroom Zone | 1 & 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| CE Mark | Yes |
| Diameter (mm) | 98 |
| Height (mm) | 110 |
| Accessories | ATL/BA |

Technical Information

| | |
|---------|-----|
| Wattage | 50W |
|---------|-----|

Technical Data - ETIM - Downlight/spot/floodlight (EC001744)

| | |
|--------------------------------------|----------------|
| Suitable for surface mounting | No |
| Suitable for built-in mounting | Yes |
| Suitable for wall mounting | No |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for traverse mounting | No |
| Suitable for pedestal/floor mounting | No |
| Suitable for light-track mounting | No |
| Adjustability | Not adjustable |
| With movement sensor | No |
| With light sensor | No |
| With light source | No |
| Suitable for number of lamps | 1 |
| Lamp holder | GU10 |
| Material housing | Aluminium |
| Colour housing | Chrome |
| Degree of protection (IP) | IP65 |
| Protection class | I |
| Max. system power | 50 W |
| Width | 170 mm |
| Height/depth | 110 mm |
| Outer diameter | 98 mm |

Datasheet generated from <https://onetimepim.com> last updated Monday, November 4, 2019 1:46:57 PM

