



LED Lowbay

- Stylish solution for medium high ceilings in retail and industry
- High efficacy of 100lm/W
- Up to 50% energy saving compared to HID solutions
- Multiple beam angles available



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Beam angle
545002000600	LEDLowbay-E 30W-4000-60D	CFL 2x26W	30	3000	100	4000	60 °

Packaging Information

Item		Box			
Item Code	Item Description	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
545002000600	LEDLowbay-E 30W-4000-60D	276x276x176	1.10	6956321806835	1

Technical Specifications

On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmable	No
Finishing	Silver
Colour rendering index CRI	≥ 80
Degree of protection (IP)	IP20
Impact strength	IK03
Protection class	I
Control gear included	Yes
Glow wire test	650 °C
Driver failure rate (at 5,000 hrs)	1 %
Weight (pc/kg)	0.54
Power factor	0.95

Electrical Supply


Frequency	50/60 Hz
Nominal voltage	220-240 V
Voltage type	AC

Mechanical Properties

Material housing	Aluminium
Optical material	Polycarbonate

Ambient Conditions

Operating temperature	-20 - 45 °C
Application temperature	25 °C
Storage environment	-30 - 50 °C



Dimensional Drawing (mm)

LEDLowbay-E 30W-4000-60D

